

AMENDMENTS TO THE CLAIMS

1. (Canceled)

2. (Currently amended) ~~A~~ The TDMA communications apparatus ~~according to claim 1 for carrying out communication using TDMA technology in which a frame is divided into a plurality of slots, a slot being treated as a unit of data transmission, and said TDMA communications apparatus performs TDMA communication while reserving slots for own transmission, said TDMA communications apparatus comprising:~~

conflict avoidance means for avoiding slot allocation conflicts with other stations by transmitting a message indicating that own station will re-reserve another slot for own transmission within a predefined period upon detecting that a slot reserved for own use has been reserved by another station as well, wherein said TDMA communications apparatus having a mode in which a slot at the same location as a current slot is reserved in each of succeeding frames, wherein the conflict avoidance means transmits a message indicating that the own station will re-reserve another slot for own transmission within the predefined period in a next frame upon detecting that a slot reserved for own use in the next frame has been reserved by another station as well.

3. (Currently amended) ~~The~~ A TDMA communications apparatus ~~according to claim 1 for carrying out communication using TDMA technology in which a frame is divided into a plurality of slots, a slot being treated as a unit of data transmission, and said TDMA communications apparatus performs TDMA communication while reserving slots for own transmission, said TDMA communications apparatus comprising:~~

conflict avoidance means for avoiding slot allocation conflicts with other stations by transmitting a message indicating that own station will re-reserve another slot for own transmission within a predefined period upon detecting that a slot reserved for own use has been reserved by another station as well, wherein said TDMA communications apparatus having a

mode in which a slot at the same location as a current slot is reserved in each of succeeding frames, wherein the conflict avoidance means transmits a message indicating that the own station will re-reserve another slot for own transmission within the predefined period in a current frame upon detecting that a next slot reserved for own use in the current frame has been reserved by another station as well.

4. (Currently amended) The TDMA communications apparatus according to claim 2 ~~one of claims 1 to 3~~, wherein the predefined period is set based on the speed of a mobile unit on which said TDMA communications apparatus is installed.

5. (Currently Amended) ~~A-The TDMA communications apparatus for carrying out communication using TDMA technology in which a frame is divided into a plurality of slots, a slot being treated as a unit of data transmission, and said TDMA communications apparatus performs TDMA communication while reserving slots for own transmission according to claim 2, wherein said TDMA communications apparatus further comprising:~~

means for evaluating the level of a signal received in each slot for a plurality of times
and

judging a slot in which the level of the received signal is less than a threshold for a specific number of times as a free slot which may be reserved for own transmission without causing a conflict with other stations.

6. (Previously presented) A TDMA communications apparatus for carrying out communication using TDMA technology in which a frame is divided into a plurality of slots, a slot being treated as a unit of data transmission, and said TDMA communications apparatus performs TDMA communication while reserving slots for own transmission, said TDMA communications apparatus comprising:

a violation information memory for storing violations of individual protocols in a

manner that allows a comparison between the content of a slot allocation table and/or database of other stations storing slot allocation status of each station and received messages.

7. (Currently Amended) A-~~The TDMA communications apparatus for carrying out communication using TDMA technology in which a frame is divided into a plurality of slots, a slot being treated as a unit of data transmission, and said TDMA communications apparatus performs TDMA communication while reserving slots for own transmission according to claim 2, wherein~~ said TDMA communications apparatus further comprising:

means for recovering a report rate by allocating a new slot within a defined next selection interval(SI) using ITDMA protocol when the communication apparatus detects that the own slot within the next SI has been erased or overridden by other stations or is not found due to a traffic situation.

8. (New) The TDMA communications apparatus according to claim 3, wherein the predefined period is set based on the speed of a mobile unit on which said TDMA communications apparatus is installed.

9. (New) The TDMA communications apparatus according to claim 3, wherein said TDMA communications apparatus further comprising:

means for evaluating the level of a signal received in each slot for a plurality of times
and

judging a slot in which the level of the received signal is less than a threshold for a specific number of times as a free slot which may be reserved for own transmission without causing a conflict with other stations.

10. (New) The TDMA communications apparatus according to claim 3, wherein said TDMA communications apparatus further comprising:

means for recovering a report rate by allocating a new slot within a defined next selection interval(SI) using ITDMA protocol when the communication apparatus detects that the own slot within the next SI has been erased or overridden by other stations or is not found due to a traffic situation.